# Thinkwell

Off Road Accessories & Hardware





# COMPANY PROFILE

Thinkwell is ISO certified professional manufacturer in Trailer & Offroad Accessories over 15 years. We have 4 advanced production line, 160 staff and more than 1500 square warehouse.

Design-Production-Packing-Shipping,our One-Stop service saves customers lots of time,cost and energy. From normal to upgraded customized parts,Thinkwell Trailer & Offroad Accessories enjoying good sales in ruling market.

We have established WIN-WIN relationship with some of world famous offroad brand from North America and Australia many years. Welcome more and more customers from all over the world.







### Thinkwell CERTIFICATE


- Over 15 years of producing experience in hardware & steel parts
- Professional design team to develop and design new parts according to customers' requirements
- Professional quality control team and advanced testing machine to insure the quality.
- · Customized parts, customized logo, and customized packing available.
- 12 months quality warranty.















#### D Ring Shackle

Part No.	Size	Working Load Limit	weignt	Dimensions(in.)				
	(in.)	(t)	(lbs.)		В	С	D	E
TKT001	1/2	2	0.72	0.81	0.63	1.88	0.5	1.31
TKT002	5/8	3-1/4	1.37	1.06	0.75	2.38	0.63	1.69
TKT003	3/4	4-3/4	2.35	1.25	0.88	2.81	0.75	2

#### Soft Shackle

Part No.	Size(A x B)	Breaking Strength (kg)	Weight (kg)
TKT004	6mm*6inch	5000	0.1
TKT005	8mm*6inch	8850	0.1
TKT006	9mm*6inch	11000	0.1
TKT007	10mm*6inch	13650	0.2
TKT008	11mm*6inch	15340	0.2
TKT009	12mm*6inch	17550	0.2
TKT010	13mm*6inch	20280	0.2
TKT011	14mm*6inch	30550	0.21





### CUSTOMIZED RECOVERY GEAR

Heavy Duty Custom Shackle



10T Suqare Mega Shackle



10T Round Mega Shackle



5T Aluminum Bow Shackle



8T Mega Bow Shackle

# 03 HITCH RECEIVER



#### **Shackle Hitch Receiver**

Process: Hitch Receiver is CNC, Shackle

is Forging

Material : Carbon Steel Surface : Powder Painted

Fitting: Shackle Isolator, Hitch Pin,

Washer etc

Part No.	Size (in.)	Work Load Limit (t)	Weight (kg)
TKT012	2	4.75	3.4



#### **Hitch Receiver**

Process: CNC

Material : Aluminum Alloy Surface : Anodic Oxidation

Fitting: Dring Shackle, Shackle

Isolator,

Hitch Pin, Washer etc

Part No.	Size (in.)	Work Load Limit (t)	Weight (kg)
TKT013	2	5	0.88



#### **Soft Shackle Hitch Receiver**

5 tons W.L.L. with 15 tons breaking strength Multi-Packing Multi-color





# OFF ROAD ACCESSORIES



5T Hitch Receiver



Custom Aluminum
Hitch Receiver



Aluminum Snatch Block



Steel Mega Snatch Block



2T Hitch Receiver



Aluminum Winch Hook



Custom Snatch Block



Custom Winch Hook



#### TOW STRAP 06



#### Tow Strap

Part No.	Size	End Fitting	Breaking Strength (lbs)
TKT017	3"*8'	Reinforced Eye	30000 lbs
TKT018	3"*20'	Reinforced Eye	30000 lbs
TKT019	3"*30'	Reinforced Eye	30000 lbs
TKT020	4"*30'	Reinforced Eye	40000 lbs



#### Axle Strap with D-Ring

Part No.	Size	Fitting	Work Load Limit (Ibs.)	Breaking Strength (lbs.)
TKT021	2"*36"	2" D Ring	3333	10000



Material:100% high tensile polyester

width: 3 inch(75mm), 2 inch(50mm), 1 inch(25mm)

length:3m to 10m or as you required



## 07 Recovery Kit







4T/8T/10T Snatch Block



3/4" D Ring Shackle



iinkwell

Hitch Lock



3"\*30ft Tow Strap



Winch Cable Dampener



Carry Bag



Qingdao Thinkwell Hardware Machinery Co., Ltd.



**Recovery Kit** 

2" Shackle Hitch Receiver 4T/8T/10T Snatch Block 3/4" D Ring Shackle Hitch Lock 3"\*30ft Tow Strap Winch Cable Dampener Carry Bag

KNell









### 09 HITCH BALL







Part NO.	Ball Dia.	Shank Dia.	Shank Length	Capacity	Finish
TKT022	1-7/8"	3/4"	1-1/2"	2000lbs	
TKT023	1-7/8"	3/4"	2"	2000lbs	
TKT024	1-7/8"	3/4"	2-3/8"	2000lbs	
TKT025	1-7/8"	3/4"	3-3/8"	2000lbs	
TKT026	1-7/8"	1"	2"	3500lbs	
TKT027	1-7/8"	1"	2-1/8"	3500lbs	
TKT028	1-7/8"	1"	2-1/2"	3500lbs	
TKT029	1-7/8"	1"	3"	3500lbs	
TKT030	1-7/8"	1"	3-3/8"	3500lbs	
TKT031	2"	3/4"	1-1/2"	3500lbs	Chrome,zinc,
TKT032	2"	3/4"	2"	3500lbs	Black Nickel,
TKT033	2"	3/4"	2-3/8"	3500lbs	Stainless
TKT034	2"	3/4"	3"	3500lbs	Steel
TKT035	2"	3/4"	3-3/8"	3500lbs	
TKT036	2"	1"	2"	6000lbs	
TKT037	2"	1"	2-3/4"	6000lbs	
TKT038	2"	1"	3"	6000lbs	
TKT039	2"	1"	3-3/8"	6000lbs	
TKT040	2-5/16"	1"	2"	6000lbs	
TKT041	2-5/16"	1"	2-1/2"	6000lbs	1
TKT042	2-5/16"	1-1/4"	2"	12000lbs	
TKT043	2-5/16"	1-1/4"	2-1/2"	12000lbs	
TKT044	2-5/16"	1-1/4"	3"	12000lbs	
TKT045	50mm	7/8"	60mm	3.5t	Chrome, Zinc
TKT046	50mm	7/8"	70mm	3.5t	Plated



Size:50mm Usage:50mm ball Material:plastic

Selecting the right hitch ball is a must for trou ble-free towing. Always use the properly rated hitch ball for your towing system. In addition to the above trailer ball, it also accept customization






Meterial: Carbon steel Size: Suit for 2"- 2-1/2"

Surface: Electrogalvanizing

Package: Bubble bag+box+carton+pallet







#### A:Rise

Distance the ball platform is set above the top of the shank

#### C:Hole size

Size of trailer ball shank that is required to fit the ball mount.

#### **B:Drop**

Distance the ball platform is set below the top of the shank.

#### D:Length

Distance form the pin hole center to the ball hole center.



#### **Hitch Ball Mounts**

Part No.	Box Size	Ball Hole Size	Drop	Rise	Length	Capacity	Finish	Shank
TKT047	2"*2"	1"	2"	3/4"	9"	6000lbs		Hollow
TKT048	2"*2"	1"	3"	2"	7-7/8"	6000lbs		Hollow
TKT049	2"*2"	1"	4"	2-3/4"	8-1/4"	6000lbs	black/	Hollow
TKT050	2"*2"	1"	5"	3-3/4"	9"	5000lbs	chrome/ zinc plated	Hollow
TKT051	2"*2"	1"	6"	4-3/4"	9-1/2"	5000lbs	611	Hollow
TKT052	2"*2"	1"	8"	6-3/4"	10"	5000lbs	0.	Hollow

#### Forged Ball Mounts

#### **TKT053**

Box Size: 2"x2" Ball Hole Size: 1-1/4"

**Drop: 2"** Rise: 1"

Length: 8-1/2" Capacity: 10000lbs

Finish: black

#### TKT054

Box Size: 2"x2" Ball Hole Size: 1-1/4"

Drop: 4" **Rise: 3"** 

Length: 9-1/4" Capacity: 10000lbs

Finish: black

#### **TKT055**

Box Size: 2"x2"

**Drop**: 6" **Rise:** 5"

Length: 10-1/4"

Finish: black

Ball Hole Size: 1-1/4

Capacity: 10000lbs

#### Hitch Ball Mounts

#### **TKT056**

Hitch Ball: 2"x1x2", 6000lbs, chrome Ball Mount: 2" drop, 6000lbs. black

Hitch Pin: dia.5/8"

#### **TKT057**

Hitch Ball: 2"x1x2", 6000lbs, chrome Ball Mount: 3" drop, 6000lbs. black

Hitch Pin: dia.5/8"

#### Welder Ball Mounts

#### **TKT058**

Box Size: 2"x2" Length: 9"

**Ball Size:** 1-7/8"

Capacity: 3500lbs

**Drop: 2"** Shank: hollow

Rise: 3/4"

#### **TKT059**

Box Size: 2"x2"

Length: 9" Ball Size:2"

Capacity: 6000lbs

Drop: 2" Shank: hollow

Rise: 3/4"

# STANDARD 12 MOUNTS



# 13 STANDARD MOUNTS



#### **TKT060**

#### Ball size:

1-7/8", 3500lbs 2", 6000lbs

2-5/16", 10000lbs

Length: 12" Shank: Hollow/ Solid



All Black/ All Chrome Ball is Chrome

Surface treatment: Chrome plated

#### **TKT061**

Box Size: 2"x2"

Ball Size: 1-7/8" & 2" Drop: 2"

Length: 8-1/4" Shank: hollow

#### **TKT062**

inkwell

Box Size: 2"x2"

Ball Size: 2" & 2-5/16"

**Drop**: 2"

Length: 8-1/4" Shank: solid



Ball is Chrome and Ball Mount is Black

## BALL MOUNTS 14





#### Adjustable Aluminum Ball Mount

#### TKT063

**Capacity:** 6000lbs **Drop:** 2" - 6" **Shank:** solid

#### TKT064

**Capacity**: 6000lbs **Drop**: 2" - 6" **Ball Size**: 2 & 2-5/16" **Shank**: solid



### Adjustable Steel Ball Mount (Type I)

#### TKT065

Capacity: 5000lbs. Box size: 2"x 2"
Max Rise: 6-1/4" Drop: 7-1/2"
Length: 13" to 12" Shank: hollow

### 15 BALL MOUNTS



Adjustable Steel Ball Mount (Type II)

#### **TKT066**

Capacity: 6000lbs

Max rise: 8-3/8"

Length: 12"

Box size: 2"x 2"

Max drop: 9-5/8"

Shank: hollow



#### Adjustable Steel Triball Mount

#### **TKT067**

**Box size**: 2"x 2" **Length**: 11-9/16"

Max Drop: 4-3/4" Shank: solid

Max Rise: 5-11/16"

Ball 1-7/8", 3500lbs, 2",6000lbs,

2-5/16", 10000lbs

Ball is Chrome Mount is Black



inkwell











Part No.	Inner Diameter (in.)	Length (in.)	Finish
TKT068	2"*2"	6	
TKO069	2"*2"	8	Disali
TKO070	2"*2"	10	Black
TKO071	2"*2"	12	

Part No.	Tube size	Length	Finish
TKT072	1-1/4" to 2"	6"	
TKT073	1-1/4" to 2"	7-1/4"	Black
TKT074	1-1/4" to 2"	10"	

Part No.	Tube Size	Length	Finish
TKT075	2" to 1-1/4"	7"	Plank
TKT076	2" to 1-1/4"	3"	Black

Part No.	Tube Size	Length	Finish
TKT077	2-1/2" to 2"	4"	Black

# 17 RECEIVER MOUNTS



#### Forged Tow Hook

Part No.	Length	Max Capacity (lbs.)	Weight(lbs.)	Shank
TKT078	7-3/8	10,000	9.02	Solid
Forge	ed Tow Ev	/P		



### Forged Tow Eye

Part No.	Length(in.)	Max Capacity (lbs.)	Weight (lbs.)	Shank
TKT079	7-3/8	10,000	9.66	Solid



#### Tow Hook with Latch

Part No.	Max Capacity (lbs.)	Breaking Strength (lbs.)	Weight (lbs.)
TKT080	10,000	15,000	1.59

### PINTLE HOOK MOUNTS 18

#### PINTLE HOOK COMBINATION HITCHES

#### **TKT081**

Htich ball 1-7/8",2000lbs,chrome
Body capacity 16000lbs, black
Mount hole spacing: 3-1/2" (left to right) x 1-3/4"
(top to bottom) ,the hole on the bottom is 1/2"
Hardware is included

#### **TKT082**

Htich ball 2",7000lbs,chrome
Body capacity 16000lbs, black
Mount hole spacing: 3-1/2" (left to right) x 1-3/4"
(top to bottom), the hole on the bottom is 1/2"
Hardware is included

#### **TKT083**

Htich ball 2-5/16",12000lbs,chrome Body capacity 16000lbs, black Mount hole spacing: 3-1/2" (left to right) x 1-3/4" (top to bottom), the hole on the bottom is 17/32" Hardware is included

#### **TKT084**

Htich ball 50mm,7000lbs,chrome Body capacity 16000lbs, black Mount hole spacing: 3-1/2" (left to right) x 1-3/4" (top to bottom), the hole on the bottom is 1/2" Hardware is included

#### PINTLE HOOK

#### **TKT085**

Capacity 5ton 3-3/8" Wide(Center to Center) 1-3/4" Up/Down (Center to Center) 17/32" Hole Diameter, Black

#### **TKT086**

Capacity 10ton 3-3/8" Wide(Center to Center) 1-3/4" Up/Down (Center to Center) 17/32" Hole Diameter, Black

#### **TKT087**

Capacity 15ton 3-3/8" Wide(Center to Center) 1-3/4" Up/Down (Center to Center) 17/32" Hole Diameter, Black

#### **TKT088**

Capacity 30ton 3-3/8" Wide(Center to Center) 1-3/4" Up/Down (Center to Center) 17/32" Hole Diameter, Black









#### ONE-PIECE PINTLE HOOK

**TKT089** 

5Ton Without hitch ball Black

**TKT090** 

Hitch ball 1-7/8", 2000lbs, chrome, The body is 12000lbs, black

**TKT091** 

Hitch ball 2", 7000lbs, chrome, The body is 12000lbs, black

**TKT092** 

Hitch ball 2-5/16", 12000lbs, chrome, The body is 12000lbs, black

### HITCH COUPLER 20




Hitch coupler for 1-7/8", 2" (2-1/2" or 3") channel width balls is galvanized to prevent corrosion and rust. It is suitable for 2"(2-1/2" or 3") channels. Suitable for 1-7/8" or 2" steel balls. In accordance with American standards.

	Part No.	Ball Dia (in.)	Channel (in.)	Max Capacity(lbs.)
	TKT093	1-7/8	2	2,000
1	TKT 094	1-7/8	2-1/2	2,000
	TKT 095	1-7/8	3	2,000
	TKT096	2	2	3,500
	TKT097	2	2-1/2	3,500
	TKT 098	2	3	3,500
	TKT 099	2	3	5,000



Part No.	Ball Size(mm)	Channel(mm)	Max Capacity(kgs.)
TKT100	50	50	3500
TKT101	50	60	3500





















#### G70 Binder Chain & Accessories

Part No.	Chain Size (in.)	Hook Size (in.)	Chain Length (in.)	Working Load Limit (lbs.)
TKT118	5/16	5/16	10	4700
TKT119	5/16	5/16	15	4700
TKT120	5/16	5/16	20	4700
TKT121	3/8	3/8	10	6600
TKT122	3/8	3/8	15	6600
TKT123	3/8	3/8	20	6600
TKT124	1/2	1/2	10	11300
TKT125	1/2	1/2	15	11300
TKT126	1/2	1/2	20	11300



#### G30 Safety Chain

Part No.	Size (in.)	Standard	Weight (kg)	Working Load Limit (lbs.)	Breaking Strength (lbs.)
TKT127	3/16" × 48"	ASTM80	0.8	800	3200
TKT128	1/4" × 48"	ASTM80	1.5	1250	5000
TKT129	5/16" × 48"	ASTM80	2.2	1900	7600
TKT130	3/16" × 48"	NACM90	0.8	800	3200
TKT131	1/4" × 48"	NACM90	1.4	1300	5200
TKT132	5/16" × 48"	NACM90	1.9	1900	6800
TKT133	3/16" × 48"	NACM96	0.8	800	3200
TKT134	1/4" × 48"	NACM96	1.4	1300	5200



# 23 WINCH ACCESSORIES



#### **Aluminum Fairlead**

Part No.	Working Load Limit (lbs.)	Size L*W*H (mm)	Hole Spacing (mm)	Weight (g)
TKT135	2500	133*38*15	109	128
TKT136	3500	147*38*15	123	139
TKT137	4500	180*39*16	153	186
TKT138	5000	222*62*18	182	420
TKT139	6000	243*62*18	204	460
TKT140	9500	297*62*18	254	548
TKT141	10000	300*70*19	254	660
TKT142	12000	297*88*18	254	760
TKT143	12000	298*90*20	254	963
TKT144	16000	300*105*30	254	1480
TKT145	16000	335*145*23	254	1620
TKT 146	16000	310*140*30	254	2000



vvay				
Part No.	Working load Limit (lbs.)	Size L*W*H (mm)	Hole Spacing (mm)	Weight (kg)
TKT 147	2500	128*87*47	109	0.65
TKT148	2500	128*87*47	109	0.64
TKT149	3000	160*91*48	124	1.04
TKT150	3000	160*91*48	124	1.02
TKT 151	4000	190*90*58	152	1.13
TKT152	4500	203*92*60	165	1.21
TKT 153	6000	232*93*64	202	2.04
TKT154	8000	310*106*80	280	3.25
TKT 155	9500	297*124*88	254	4.2
TKT156	10000	297*126*88	254	4.3
TKT157	10000	297*123*88	254	4.28
TKT 158	10000	305*105*45	278	2.36
TKT 159	16000	298*129*88	254	5.12
	TKT147 TKT148 TKT149 TKT150 TKT151 TKT152 TKT153 TKT154 TKT155 TKT156 TKT157 TKT157	Part No.         (lbs.)           TKT147         2500           TKT148         2500           TKT149         3000           TKT150         3000           TKT151         4000           TKT152         4500           TKT153         6000           TKT154         8000           TKT155         9500           TKT156         10000           TKT157         10000           TKT158         10000	Part No.         (lbs.)         (mm)           TKT147         2500         128*87*47           TKT148         2500         128*87*47           TKT149         3000         160*91*48           TKT150         3000         160*91*48           TKT151         4000         190*90*58           TKT152         4500         203*92*60           TKT153         6000         232*93*64           TKT154         8000         310*106*80           TKT155         9500         297*124*88           TKT156         10000         297*126*88           TKT157         10000         305*105*45	Part No.         (lbs.)         (mm)         (mm)         (mm)           TKT147         2500         128*87*47         109           TKT148         2500         128*87*47         109           TKT149         3000         160*91*48         124           TKT150         3000         160*91*48         124           TKT151         4000         190*90*58         152           TKT152         4500         203*92*60         165           TKT153         6000         232*93*64         202           TKT154         8000         310*106*80         280           TKT155         9500         297*124*88         254           TK156         10000         297*126*88         254           TKT157         10000         297*123*88         254           TKT158         10000         305*105*45         278



#### Clevis Slip Hook with Latch

Part No.	Size Of Chain	Working L		Weight	Di	mension(in	.)
	(in.)	H-331	A-331	(lbs.)	В	Е	Р
TKT160	1/4	1,950	2,750	0.5	0.44	0.79	0.38
TKT161	5/16	2,875	4,300	0.75	0.5	0.93	0.44
TKT162	3/8	4,000	5,250	1.2	0.59	1.14	0.47
TKT163	7/16	5,000	7,000	2.06	0.66	1.18	0.56
TKT164	1/2	6,500	9,000	2.8	0.75	1.42	0.63
TKT165	5/8	9,250	13,500	5.18	0.91	1.65	0.75
TKT166	3/4	12,500	19,250	10.45	1.31	1.81	. 1
TKT167	1	17,600	26,500	13.65	1.38	1.98	1.14



Winch Line Stopper

Material: Heavy-duty silicone rubber Center hole size: diameter 1/2 inch (12mm) Dimensions: 2.44 x 2.44 x 1.88 inches

(6.2 x 6.2 x 4.77 cm)

Multiple colors are available: black, red, orange,

green, yellow, etc.





#### Farm Jack

Part No.	Working Load Limit (kg)	Size	Min.H	Max.H	Weight (kg)
TKT168	3000	20"	153mm	680mm	12
TKT 169	3000	33"	153mm	700mm	13
TKT170	3000	48"	154mm	1070mm	14
TKT171	3000	60"	155mm	1350mm	15



#### Farm Jack Mate

		Farm Jack Mate				
Part No.	Working Load Limit (kg)	Size	Min.H	Max.H	Weight (kg)	
TKT172	3000	20"	153mm	680mm	12	
TKT 173	3000	33"	153mm	700mm	13	
TKT 174	3000	48"	154mm	1070mm	14	
TKT175	3000	60"	155mm	1350mm	15	



#### Farm Jack Base

Part No.	Length(mm)
TKT176	400



SIZE:1066.8\*355.6\*50.8



Material: High Quality polyethylene Nylon material has advantages of toughness,tensile strength, compressive strength, anti-fatigue, anitcorrosion.thermostability and UV resistance. Heavy Duty and UV-Resistant.Anti-tarnishing.

Loading capacity: Sand / snow / mud grips on underside of track for non-slip applications Can accommodate vehicles up to 10 tons.Bottom bending-proof ,cruciform grip ground design makes the product more firm, more solid in ground gripping.



SIZE: 950\*280\*50mm